

**HC-126 AWNING
Thermal Performance Ratings**

MODEL CODE	LAYERS OF GLAZING	SHGC	U-FACTOR Btu/hft. F	U-FACTOR W/m2. K	ER	VT-Visible Transmittance 0 to 0.99
180 ESC-Arg-i89	2	0.41	0.23	1.31	35	0.49
180 ESC-Arg-CI-Arg-180 ESC	3	0.38	0.21	1.17	36	0.44
180 ESC-Arg-CI-Arg-180 ESC (With Grilles)	3	0.34	0.21	1.19	33	0.40
180 ESC-Arg-180 ESC-Arg-i89	3	0.36	0.19	1.08	37	0.43
180 ESC-Arg-180 ESC-Arg-i89 (With Grilles)	3	0.32	0.19	1.09	34	0.39
180 ESC-Arg-Kry-180 ESC-Arg-Kry-i89	3	0.36	0.18	0.99	39	0.43
180 ESC-Arg-Kry-180 ESC-Arg-Kry-i89 (With Grilles)	3	0.32	0.18	1.01	36	0.39

 Energy Star  Energy Star Most Efficient

STRUCTURAL RATINGS

AAMA/WDMA/CSA 101/I.S.2/A440-11 AND A440S1-19 | Size Tested: 1220 · 1040mm (48" x 41") | LC-PG70
 Positive Design Pressure = +3360 Pa (+70 psf) | Negative Design Pressure = -3360 Pa (-70 psf)
 Water Test Pressure: 510Pa | Canadian Air Infiltration/Exfiltration: A3

