

Heritage Maximum

COLLECTION

HC-451 SLIM FIXED Thermal Performance Ratings

MODEL CODE	LAYERS OF GLAZING	SHGC	U-FACTOR Btu/hft. F	U-FACTOR W/m2. K	ER	VT-Visible Transmittance 0 to 0.99
180 ESC-Arg-Cl	2	0.59	0.27	1.51	41	0.70
180 ESC-Arg-Cl (With Grilles)	2	0.53	0.27	1.51	37	0.63
180 ESC-Arg-i89	2	0.57	0.22	1.23	46	0.68
180 ESC-Arg-i89 (With Grilles)	2	0.51	0.22	1.23	42	0.61
180 ESC-Arg-Cl-Arg-180 ESC	3	0.52	0.19	1.08	46	0.62
180 ESC-Arg-Cl-Arg-180 ESC (With Grilles)	3	0.47	0.20	1.12	42	0.56
180 ESC-Arg-Cl-Arg-i89	3	0.52	0.20	1.16	44	0.63
180 ESC-Arg-Cl-Arg-i89 (With Grilles)	3	0.47	0.21	1.19	41	0.56

Energy Star
 Energy Star Most Efficient

STRUCTURAL RATINGS

AAMA/WDMA/CSA 101/I.S.2/A440-11 AND A440S1-19 | Size Tested: 1829 x 2134mm (72" x 84") | CW-PG70
 Positive Design Pressure = +3600 Pa (+75 psf) | Negative Design Pressure = - 3600 Pa (-75 psf)
 Water Test Pressure: 730Pa | Canadian Air Infiltration/Exfiltration: Fixed

