

**WC-150 Slim Fixed
Thermal Performance Ratings**

MODEL CODE	LAYERS OF GLAZING	SHGC	U-FACTOR Btu/hft. F	U-FACTOR W/m2. K	ER	VT-Visible Transmittance 0 to 0.99
180 ESC-Arg-Cl	2	0.55	0.28	1.60	37	0.65
180 ESC-Arg-Cl (With Grilles)	2	0.49	0.28	1.60	33	0.58
180 ESC-Arg-i89	2	0.53	0.24	1.35	41	0.63
180 ESC-Arg-i89 (With Grilles)	2	0.48	0.24	1.35	38	0.56
180 ESC-Arg-Cl-Arg-180 ESC	3	0.48	0.21	1.21	41	0.57
180 ESC-Arg-Cl-Arg-180 ESC (With Grilles)	3	0.43	0.22	1.25	37	0.51
180 ESC-Arg-Cl-Arg-i89	3	0.48	0.22	1.26	40	0.58
180 ESC-Arg-Cl-Arg-i89 (With Grilles)	3	0.43	0.23	1.32	36	0.52
Cl-Arg-180	2	0.56	0.28	1.61	37	0.64
Cl-Arg-180, (With Grilles)	2	0.51	0.29	1.65	33	0.58
180-Arg-Cl	2	0.53	0.28	1.61	35	0.64
180-Arg-Cl, (With Grilles)	2	0.51	0.29	1.65	32	0.58
180-Arg-Cl	2	0.59	0.31	1.77	35	0.62
180-Arg-Cl, (With Grilles)	2	0.53	0.32	1.81	31	0.56
180-Arg-i89	2	0.51	0.24	1.34	40	0.63
180-Arg-i89, (With Grilles)	2	0.46	0.24	1.34	37	0.56
Lami-Arg-180	2	0.51	0.29	1.66	33	0.63

Structural Ratings

AAMA/WDMA/CSA 101/I.S.2/A440-11 and A440S1-17 | Size Tested: 1829 x 2134 mm (72 "x 84") | CW-PG70
 Positive Design Pressure (DP) = +3360 Pa (+70 psf) 3360 Pa (-70 psf)
 Water Test Pressure: 720Pa | Canadian Air Infiltration/Exfiltration: Fixed

