

**WC-150 SLIM FIXED  
Thermal Performance Ratings**

MODEL CODE	LAYERS OF GLAZING	SHGC	U-FACTOR Btu/hft. F	U-FACTOR W/m2. K	ER	VT-Visible Transmittance 0 to 0.99
180 ESC-Arg-Cl	2	0.55	0.29	1.63	36	0.65
180 ESC-Arg-i89	2	0.53	0.24	1.35	41	0.64
180 ESC-Arg-i89 (With Grilles)	2	0.48	0.24	1.35	38	0.57
180 ESC-Arg-Cl-Arg-180 ESC	3	0.48	0.21	1.18	42	0.58
180 ESC-Arg-Cl-Arg-180 ESC (With Grilles)	3	0.44	0.22	1.23	38	0.52
180 ESC-Arg-180 ESC-Arg-i89	3	0.46	0.19	1.06	43	0.56
180 ESC-Arg-180 ESC-Arg-i89 (With Grilles)	3	0.41	0.19	1.10	39	0.50

Energy Star      Energy Star Most Efficient

**STRUCTURAL RATINGS**

AAMA/WDMA/CSA 101/I.S.2/A440-11 AND A440S1-19 | Size Tested: 1829 x 2134mm (72" x 84") | CW-PG70  
 Positive Design Pressure = +2160 Pa (+45 psf) | Negative Design Pressure = - 2160 Pa (-45 psf)  
 Water Test Pressure: 720Pa | Canadian Air Infiltration/Exfiltration: Fixed

