

**WC-250 DOUBLE SLIDER TILT
Thermal Performance Ratings**

| MODEL CODE | LAYERS OF GLAZING | SHGC | U-FACTOR Btu/hft. F | U-FACTOR W/m2. K | ER | VT-Visible Transmittance 0 to 0.99 |
|---|-------------------|------|------------------------|---------------------|----|--|
| 180 ESC-Arg-i89 | 2 | 0.48 | 0.25 | 1.40 | 35 | 0.58 |
| 180 ESC-Arg-CI-Arg-180 ESC | 3 | 0.44 | 0.22 | 1.27 | 35 | 0.52 |
| 180 ESC-Arg-180 ESC-Arg-i89 | 3 | 0.41 | 0.20 | 1.16 | 36 | 0.51 |
| 180 ESC-Arg-180 ESC-Arg-i89 (With Grilles) | 3 | 0.37 | 0.21 | 1.20 | 33 | 0.45 |
| 180 ESC-Arg-Kry-180ESC-Arg-Kry-i89 | 3 | 0.41 | 0.19 | 1.07 | 38 | 0.51 |
| 180 ESC-Arg-Kry-180ESC-Arg-Kry-i89 (With Grilles) | 3 | 0.37 | 0.19 | 1.09 | 35 | 0.45 |

 Energy Star  Energy Star Most Efficient

STRUCTURAL RATINGS

AAMA/WDMA/CSA 101/I.S.2/A440-11 AND A440S1-19 | Size Tested: 1600 x 1100mm (63" x 43") | R-PG25
 Positive Design Pressure = +2160 Pa (+45 psf) | Negative Design Pressure = -2160 Pa (-45 psf)
 Water Test Pressure: 180Pa | Canadian Air Infiltration/Exfiltration: A2

