

**WC-300 Single Slider Lift Out
Thermal Performance Ratings**

MODEL CODE	LAYERS OF GLAZING	SHGC	U-FACTOR Btu/hft. F	U-FACTOR W/m2. K	ER	VT-Visible Transmittance 0 to 0.99
180 ESC-Arg-Cl	2	0.47	0.28	1.58	32	0.56
180 ESC-Arg-Cl (With Grilles)	2	0.42	0.28	1.58	29	0.49
180 ESC-Arg-i89	2	0.45	0.24	1.36	36	0.54
180 ESC-Arg-i89 (With Grilles)	2	0.41	0.24	1.36	34	0.48
180 ESC-Arg-Cl-Arg-180 ESC	3	0.41	0.22	1.24	36	0.59
180 ESC-Arg-Cl-Arg-180 ESC (With Grilles)	3	0.37	0.22	1.27	33	0.44
180 ESC-Arg-Cl-Arg-i89	3	0.41	0.23	1.29	35	0.50
180 ESC-Arg-Cl-Arg-i89 (With Grilles)	3	0.37	0.23	1.33	32	0.44
Cl-Arg-180	2	0.48	0.28	1.59	33	0.56
Cl-Arg-180, (With Grilles)	2	0.43	0.29	1.63	29	0.49
Cl-Arg-LOF	2	0.51	0.30	1.73	31	0.54
180-Arg-i89	2	0.44	0.24	1.35	35	0.54
180-Arg-i89, (With Grilles)	2	0.39	0.24	1.35	33	0.48
Lami-Arg-180	2	0.44	0.29	1.65	29	0.54

Structural Ratings

AAMA/WDMA/CSA 101/I.S.2/A440-08 and A440S1-14 | Size Tested: 1600 x 1110 mm (63" X 44") | R-PG35
 Positive Design Pressure = +2640 Pa (+55 psf) | Negative Design Pressure = -2640 Pa (-55 psf)
 Water Test Pressure: 160Pa | Canadian Air Infiltration/Exfiltration: A3

