

**WC-325 Single Slider Lift Out
Thermal Performance Ratings**

MODEL CODE	LAYERS OF GLAZING	SHGC	U-FACTOR Btu/hft. F	U-FACTOR W/m2. K	ER	VT-Visible Transmittance 0 to 0.99
180 ESC-Arg-Cl	2	0.39	0.28	1.61	25	0.64
180 ESC-Arg-Cl (With Grilles)	2	0.49	0.28	1.61	31	0.57
180 ESC-Arg-i89	2	0.52	0.24	1.37	38	0.63
180 ESC-Arg-i89 (With Grilles)	2	0.47	0.24	1.37	35	0.56
180 ESC-Arg-Cl-Arg-180 ESC	3	0.47	0.22	1.23	38	0.57
180 ESC-Arg-Cl-Arg-180 ESC (With Grilles)	3	0.43	0.22	1.26	35	0.51
180 ESC-Arg-Cl-Arg-i89	3	0.48	0.23	1.28	38	0.57
180 ESC-Arg-Cl-Arg-i89 (With Grilles)	3	0.43	0.23	1.33	34	0.51
Cl-Arg-180	2	0.56	0.28	1.60	37	0.64
Cl-Arg-180, (With Grilles)	2	0.50	0.28	1.60	34	0.57
180-Arg-Cl	2	0.52	0.28	1.60	35	0.64
180-Arg-Cl, (With Grilles)	2	0.47	0.28	1.60	32	0.57
180-Arg-i89	2	0.51	0.24	1.36	39	0.63
180-Arg-i89, (With Grilles)	2	0.46	0.24	1.36	36	0.56
Lami-Arg-180	2	0.50	0.29	1.67	32	0.63

Structural Ratings

AAMA/WDMA/CSA 101/I.S.2/A440-08 and A440S1-14 | Size Tested: 1600x 1100mm (63" x 43") | R-PG25
 Positive Design Pressure = +1920 Pa (+40 psf) | Negative Design Pressure = -1920 Pa (-40 psf)
 Water Test Pressure: 180Pa | Canadian Air Infiltration/Exfiltration: A2

